

CAR4A

Car Adapter DC/DC



Features:

- Wide input voltage range
- Max. output power 72.00W
- Car/Truck input connector

Applications:

Suitable for use with tablet PC's, netbooks, handheld devices (e.g. scanner, RFID devices) etc.

Specification

Input		
Voltage range	10.50 – 32.00VDC	
Stand-by current	Typical 77.00mA @ 10.50V input Typical 54.00mA @ 32.00V input	
Input fuse	10.00A	
Protection	Reverse polarity (input fuse) Under voltage protection (Transient suppression circuit)	
Output		
Voltage range	3.00 – 24.00V nominal	
Power	60.00W cont. 72.00W max.	
Initial set tolerance	±5% max.	
Load regulation	-100mV max. / A	
Line regulation	±1% max.	
Ripple & Noise	< 300.00mV _{pk-pk}	
Current limit	Constant current, 4.00A max.	
Protection	Short circuit, over temperature, over voltage	
Environmental		
	Operation:	Storage:
Ambient Temperature	-20°C to 35°C 35°C to 50°C, derating 35%	-40°C to 85°C
Pressure & Altitude	1200hPa to 570hPa max. 4600m above sea level	1200hPa to 115hPa max. 15000m above sea level
Humidity (non-condensing)	5% to 95% r.H.	5% to 95% r.H.
General		
Input connector	Cigarette lighter adapter	
Output connector	Customer-specific	
Efficiency	Typical 86% at 100% load	
MTBF	20000h @ 25°C ambient temperature and G _B per MIL HDBK217F	
Green procurement	RoHS 2011/65/EU + 2015/863/EU REACH 1907/2006 WEEE 2012/19/EU	
Indicator	Single green LED	
Ingress protection rating	IEC60529, IP40	
Cooling	Convection cooled	
Safety & EMC		
Regulatory approvals	Europe United Kingdom USA/Canada Australia	CE UKCA UL60950-1 RCM
Electromagnetic Emissions	Europe	EN55011/EN55022 class B, EN55024, EN55014-1 FCC15 class B
Electromagnetic Immunity	USA	IEC61000-4-2, 4kV contact, 8kV air IEC61000-4-3, 80-1000MHz, 10V/m, AM 80% 1kHz, PM ED50% 200Hz
	Electrical fast transient/burst immunity test	IEC61000-4-4, +/-1kV, 5/50ns
	Surge immunity test	IEC61000-4-5, +/-0,5kVsym, 1.2/50(8/20)µs
	Conducted Immunity	IEC61000-4-6, 0.15-80MHz, 10V, 80%, 1KHz, AM, CDN-M2
	Immunity Impulse	IEC61000-6-1 DIN40839 part 1

Mechanical Details	
Housing dimensions (LxWxH)	111.00 x 48.00 x 35.00mm, without cables and connectors
Input cable length	100cm ±5%
Output cable length	100cm ±5%
Weight	Approx. 200g, without cables, connectors and wall-mount kit

Germany/Headquarters

RRC power solutions GmbH
Technologiepark 1
66424 Homburg / Saar

Tel.: +49 6841 98090
Fax: +49 6841 9809280
Email: sales@rrc-ps.de
Web: www.rrc-ps.com

USA

RRC power solutions Inc.
18340 Yorba Linda Blvd.,
107-437
Yorba Linda, CA 92886

Tel.: +1 714 777 3604
Fax: +1 714 777 3658
Email: usa@rrc-ps.com
Web: www.rrc-ps.com

Hong Kong

RRC power solutions Ltd.
S-V,6/F, Valiant Industrial
Centre 2-12 Au Pui Wan Street
Fo Tan, N.T., Hong Kong

Tel.: +852 2376 0106
Fax: +852 2375 0107
Email: hkrrc@rrc-ps.cn
Web: www.rrc-ps.cn

China

RRC power solutions Ltd.
Room 1306, C Building,
Tianan International building,
Renmin South Road, Luohu
District, Shenzhen 518021

Tel.: +86 755 8374 1908
Fax: +86 755 8374 1861
Email: hkrrc@rrc-ps.cn
Web: www.rrc-ps.cn