

RRC2130

Standard Battery Pack Li-Ion
7.20V / 4.17Ah / 30.02Wh



Picture only for reference



Features

- Worldwide approvals and certification of safety standards
- No development costs, fast time-to-market
- Smart batteries with numerous features according to the SMBus specification
- State-of-the-art lithium-ion cells with the market’s highest energy density
- High discharge performance
- JEITA charging profile optimization
- Numerous and redundant safety features
- Increased ESD protection up to 8.00kV
- Up to 80% of initial capacity after 800 cycles

Applications

Suitable for use in slim devices for industrial and medical applications, etc.

Specification






General	
Delivery status battery capacity	<30%
Compliance information	IEC 62133 / CE / UL2054 / FCC / UKCA / PSE / KC / BSMI / GOST-R / CMIM / CQC / RCM / BIS / TISI / UN 38.3 / RoHS / REACH
Operating temperature	0°C to 45°C (charge) -20°C to 60°C (discharge)
Storage temperature	-20°C to 50°C max. -20°C to 25°C recommended
PN	110088

Electrical Parameters	
Nominal voltage	7.20V
Nominal capacity	4.17Ah
Initial impedance	<180mΩ @ 1kHz at 25°C
Max. charge current	2.70A
Max. charge voltage	8.40V
Max. discharge current	6.00A

Battery Dimensions	
Length	150.60mm +0.50/-0.50
Width	86.20mm +0.40/-0.40
Thickness	8.35mm +0.25/-0.25
Weight	172g
Contacts	+, +, C, D, T, -, -
Ingress protection	IP40

Safety Features	
CUV (Cell Under Voltage)	Protection against deep discharge
COV (Cell Over Voltage)	Protection against over charge
OTC (Over Temperature in Charge)	Protection against overheating while charging
OTD (Over Temperature in Discharge)	Protection against overheating during discharging

Recommended Accessories

Type	Product	P/N	Application
Standard Battery Charger	 RRC-SMB-FPC	110083	40.00W standard battery charger for optimized charging process with external power supply for world-wide use.
Power Supply AC/DC	 PS65	210919	External power supply (worldwide use) for embedded battery charger RRC-PMM240 or for mobile devices. Included in RRC-SMB-FPC.
AC Power Cable	 US-Version EU-Version UK-Version AU-Version CN-Version	210950 210951 211333 211334 211959	Country specific power cable for PS65.
Car Adapter DC/DC	 RRC-SMB-CAR	110041	90.00W car adapter with USB charging port. Power supplying in cars and trucks for RRC-SMB-FPC, RRC-PMM240 or mobile devices
Battery Mating Connector	 RRC-MC21-90-10 RRC-MC21-90-20	211268 211278	Mating Connector for standard smart batteries RRC2130, RRC2140. Available for 90° PCB mounting (top and edge).

Germany/Headquarters

RRC power solutions GmbH
Technologiepark 1
66424 Homburg / Saar

Tel.: +49 6841 98090
Fax: +49 6841 9809280
Email: sales@rrc-ps.de
Web: www.rrc-ps.com

USA

RRC power solutions Inc.
18340 Yorba Linda Blvd.,
107-437
Yorba Linda, CA 92886

Tel.: +1 714 777 3604
Fax: +1 714 777 3658
Email: usa@rrc-ps.com
Web: www.rrc-ps.com

Hong Kong

RRC power solutions Ltd.
S-V,6/F, Valiant Industrial
Centre 2-12 Au Pui Wan Street
Fo Tan, N.T., Hong Kong

Tel.: +852 2376 0106
Fax: +852 2375 0107
Email: hkrrc@rrc-ps.cn
Web: www.rrc-ps.cn

China

RRC power solutions Ltd.
Room 1306, C Building,
Tianan International building,
Renmin South Road, Luohu
District, Shenzhen 518021

Tel.: +86 755 8374 1908
Fax: +86 755 8374 1861
Email: hkrrc@rrc-ps.cn
Web: www.rrc-ps.cn